



REM5000R1001/U

Portable Comfort Control

Overview

Use the Portable Comfort Control anywhere in the home to experience a new level of comfort and convenience. Works in both zoned and non-zoned applications.

Features

- Powered by RedLINK™ reliability
- No interference with other wireless devices in the home
- Works with compatible RedLINK™ enabled thermostats and accessories
- Installs in minutes
- Touchscreen interface with backlit display
- Can display outdoor temperature and humidity
- Built-in pager with an audible noise helps locate the device in the home
- Screen-lock feature helps prevent accidental changes
- 1 year battery life
- 2 month low battery warning
- In Non-Zoned Applications:
 - Bring it with you anywhere in the home to sense and control temperature from the room that you are in.
- In Zoned Applications:
 - View and adjust all RedLINK™ enabled thermostats from a single control.
 - Controls up to 16 thermostats

Product Specifications

Application	Zoned and Non-Zoned Applications
Dimensions (in.)	6 1/4 in. high x 3 1/8 in. wide x 1 5/8 in. deep
Dimensions (mm)	159 mm high x 79 mm wide x 41 mm deep
Used With	RedLINK™ enabled thermostats and accessories
Comments	Portable Comfort Control is also available in kits.
Operating Humidity Range (% RH)	5 to 90% RH, non-condensing
Operating Temperature Range (F)	32 F to 120 F
Operating Temperature Range (C)	0 C to 48.9 C
Sensor Element	Thermistor
Differential Temperature (F)	± 1 F
Differential Temperature (C)	±0.5 C
Power Method	Battery
Changeover	Auto or Manual